DATA SHEET

AMILO DISPLAY L 3190T
Economy Widescreen

Issue: **April 2009**

An attractive price doesn't mean that you have to compromise on style or performance. Thanks of latest panel technology the AMILO Display L 3190T save up to 50% power consumption in operating mode.

Reduced power consumption up to 50% and power management according to EPA

Excellent color purity and well balanced brightness uniformity

Fast response time (typ.) of 5 ms, perfect for Internet, home office, multitasking and more

19" widescreen class display in optimum 16:9 movie format

Theme mode for optimized picture

Due to integrated speakers no further accessories needed

ENERGY STAR

CERTIFIED FOR Windows Vista®

5ms RESPONSE TIME

5000:1 ACR CONTRAST

SPEAKER

AMILO Display L 3190T

Special features	
	Aspect ratio conversion, cable guide
Stand details	
Stand	removable
Tilt angle	-5° / +15°
Picture performance	
Contrast - advanced	5000:1
Response time black to black typical	5 ms
Viewing angle (h/v)	170° / 170°
Color performance	16.7 Mio colors (Hi-FRC)
Brightness - typical	300 cd/m²
Size and resolution	
Aspect ratio	16:9
Diagonal Size	18.5-inch (47 cm)
Resolution (native)	1366 x 768 pixel (recommended)
Resolution (interpolated)	1360 x 768 pixel, 1280 x 1024 pixel, 1024 x 768 pixel
Picture size	409.8 x 230.4 mm
Pixel Pitch	0.3 mm
Frequencies	
Horizontal	28 - 81.1 kHz
Vertical	56 - 75 Hz
Frequencies - bandwidth	140 Mhz
Connectivity	
Video input	1 x D-SUB
Audio sound output	2 x 1 W
Audio signal input	3.5 mm stereo phone jack
OSD Languages and setting options	
Languages	Czech, Danish, Dutch, English, Finish, French, German, Hungarian, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Brightness / Contrast	Brightness, Contrast
Color	Cold, Warm, Custom Color
Image adjust	Clock, H-Position, V-Position, Expansion
Audio	Mute, Volume
Information	Resolution/mode, Signal input
Mode	General, Movie, Picture, Game
Power consumption (typical, w/o sound)	
Soft switch off	0.6 W
Power save mode	0.8 W
Operating with EPA settings	15 W
Operating maximum brightness	20 W
Electrical values	
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Protection class	1
Compliance	
Europe	CE

Compliance	
USA/Canada	FCC Class B, cUL
Australia&New Zealand	C-Tick
Russia	GOST
Saudi Arabia	SASO
Global	ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Quality and Reliability	
MTBF (demonstrated)	50000 h

Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	440 x 62.7 x 281.5 mm
Dimension with stand (W x D x H)	440 x 189 x 351.3 mm
Weight (packed)	4.7 kg
Weight (unpacked)	3.4 kg
Weight (Monitor only)	
Operating ambient temperature	5 - 35°C

Miscellaneous	
	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock

Package content	
	Data cable 1.8m, D-SUB (15-pin), Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, User manual, Warranty booklet

Order code	
SAP order name	AMILO LL 3190T
Order Code	S26361-K1301-V180
EAN Code	4333643572440

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions April 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com/